


Building with conscience.



Sto DrainScreen is a drainage mat composed of a polyester nylon fabric that is highly permeable and therefore allows trapped moisture to dry out faster. No matter how tight the wall assembly is, moisture may find a way in and it is crucial to design a system that provides a path for the moisture to escape. Any cracks or gaps in cement-based wall claddings or in mortar joints of masonry systems are potential entry points for moisture. Trapped moisture is a source of mold and rot and may lead to structural failures of the wall assembly. Therefore, designing a system that includes Sto DrainScreen provides continuous ventilation and drainage to remove incidental moisture and helps protect the integrity of the wall assembly. When combined with StoGuard® air and water-resistive barrier, Sto DrainScreen offers the optimal protection against moisture intrusion.



StoPowerwall® Drainscreen® with Sto Crack Defense option



A highly permeable mat for superior moisture protection

Sto DrainScreen may be used in non-Sto systems behind stucco, masonry, stone, thin veneer and siding. Sto DrainScreen is an integral component of Sto's fully engineered stucco and cement board systems - StoPowerwall® DrainScreen and StoQuik® Silver DrainScreen.



Product & Technical Data		
Thickness	6 mm (nominal ¼") 10 mm (nominal 3/8")	
Color	Yellow	
Coverage	Sto DrainScreen 6mm: 4 x 62.5 ft roll = 250 ft ² (1.2 x 19 m = 23 m ²) Sto DrainScreen 10mm: 4 x 75 ft roll = 300 ft ² (1.2 x 23 m = 28 m ²)	
Surface Burning – ASTM E84	Class A Flame Spread < 25 Smoked Developed < 75	
Building Code	Meets requirements of NFPA 285 for use on all Types of	

construction; refer to ICC ESR 1233

Features	Benefits
Polyester nylon fabric	Highly permeable, faster drying of the wall
Sturdy fabric and filaments	Integrity of drainage plane will not be compromised when fastened
Engineered filament pattern	Allows multi-directional drainage
Lightweight	Easy to handle, carry and roll onto the wall
Flexible material	Conforms to irregular surfaces and corners with complete and effective coverage
Breathable fabric	Prevents stucco or mortar from obstructing the drainage plane
48" wide rolls	Reduces the number of seams
6mm and 10mm thick rolls	To accommodate specifiers' requirements

Sto Americas

Sto Corp.

Compliance

3800 Camp Creek Pkwy Building 1400, Suite 120 Atlanta, GA 30331 USA

Phone 1-800-221-2397 www.stocorp.com

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.