
Sto HP Colorants

81184 Sto HP Colorants



Technical Data		Hig
REPORT	TEST RESULTS	use Co
Gravimetric tinting strength	+/- 2%	00
Volumetric Tinting Strength	+/- 3%	
dH (Hue)	+/- 0.4%	Pa
dC (Chroma)	+/- 0.6%	1 (
Complies with US EPA (40 CER 50) an	od South Coast AOMD (Rule 1113) VOC emission standards for	Sh

59) and South Coast AQMD (Rule 1113) VOC emission standards for colorants. VOC less than 50 g/L.

Features & Benefits

- 1 **Excellent durability**
- 2 Binder-free aqueous pigment preparation for water-based decorative paints
- 3 Manufactured without using alkyl phenol ethoxylated (APEO) additives
- 4 Suitable for manual and automatic dispensing equipment
- 5 Narrow tolerances of shade and color strength for exact color reproduction
- 6 Miscible in all proportions with each other pigment preparation of the Sto Color Charts

Mixing

STIR THOROUGHLY, OR SHAKE THREE MINUTES. EMPTY CONTAINER THOROUGHLY, SCRAPE SIDES. ALLOW CAN TO AIR DRY BEFORE DISPOSAL. FOR COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

Health and Safety

FIRST AID MEASURES

Eye Contact: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. Skin Contact: Wash thoroughly with soap and water for 15 minutes. If skin irritation occurs, seek medical attention. Inhalation: Move the victim to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical advice/attention. Never give anything by mouth to an unconscious person. Ingestion: If swallowed: If swallowed, DO NOT induce vomiting. Do not give anything to drink. Call a physician immediately. Note to Physicians: None known. Other First Aid: General advice: Get medical advice/attention if you feel unwell.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations. Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet for further health and safety information. Safety Data Sheet (SDS) is available for download at www.stocorp.com

LIMITED WARRANTY

This product is subject to a written limited warranty which can be obtained free of charge from Sto Corp. Sto offers written UV Fade Resistance warranties. Please contact your Sto Sales Representative for more details.

Sto Corp.

3800 Camp Creek Parkway Building 1400, Suite 120 Atlanta, GA 30331

Tel: 404-346-3666 Toll Free: 1-800-221-2397 Fax: 404 346-3119

PB 81184 Revision: A1.0 Date: 06/2017

Attention

Attention This product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product, and to the structure of the building or its components. <u>STO CORP. DISCLAIMS ALL WARRANTIES</u> <u>EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WARTRET ISSUED TO AND ACCEPTED BY</u> <u>BUILDING CONTERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM</u> <u>TIME TO TIME</u>. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties. cautions and disclaimers of lease refer to the Sto Corn website. rranties, cautions and disclaimers, please refer to the Sto Corp. website, www.st

h Performance Colorants for in all Sto Finishes and tings.

kaging

uart (0.95L)

Shelf Life

2 years

Storage

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Keep away from flames and sparks. Protect from extreme heat [90°F (32°C)], freezing, and direct

sunlight.

www.stocorp.com