

ARMAT Classic Plus

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Date of Issue: 10/28/2020



Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: ARMAT Classic Plus Product Code: 81738

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Sto Corp.
3800 Camp Creek Pkwy
Bldg 1400, Ste 120
Atlanta, GA 30331
404-346-3666
www.stocorp.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Skin Sens. 1A H317

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms(GHS-US) :



GHS07

Signal Word (GHS-US) :

Warning

Hazard Statements(GHS-US) :

H317 - May cause an allergic skin reaction.

Precautionary Statements(GHS-US) :

P261 - Avoid breathing vapors, mist, or spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, and eye protection.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see section 4 on this SDS).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. This product contains Crystalline Silica and titanium dioxide dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica and titanium dioxide dust may cause lung damage in the form of silicosis, lung cancer, chronic kidney disease, or respiratory irritation.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Water	AQUA / water	(CAS-No.) 7732-18-5	18-25	Not classified
Quartz	Quartz (SiO ₂) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz	(CAS-No.) 14808-60-7	15-20	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aluminumhydroxide (Al(OH)3)	C.I. 77002 / Alumina trihydrate / Aluminum trihydroxide	(CAS-No.) 21645-51-2	10	Not classified
Limestone	Chalk / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Ground limestone / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl	(CAS-No.) 1317-65-3	24 – 25	Not classified
Acrylic polymers		(CAS-No.) 9065-11-6	6.– 7	Not classified
Talc (Mg3H2(SiO3)4)	Talc / Magnesium silicate / Talc (containing no asbestos fibers) / Talc (containing no asbestos) / Magnesium silicate, hydrous / Asbestiform talc	(CAS-No.) 14807-96-6	2.5 – 3	STOT RE 1, H372
Carbonicacid, magnesiumsalt (1:1)	Magnesium carbonate / C.I. 77713	(CAS-No.) 546-93-0	1.75 – 2.25	Not classified
Perlite	Perlite, expanded / Perlit	(CAS-No.) 93763-70-3	≤ 1.5	Not classified
2,2,4-Trimethylpentan-1,3-diol monoisobutyrate	Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol / Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	(CAS-No.) 25265-77-4	<1	AquaticAcute 3, H402
Titanium dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO2) / CI 77891 / Titanium(IV) oxide	(CAS-No.) 13463-67-7	≤ 0.4	Carc. 2, H351
Glass, oxide, chemicals	Glass, oxide / Glass / Sodium calcium polyphosphate / Glass powder / Calcium sodium polyphosphate	(CAS-No.) 65997-17-3	< 0.3	Not classified
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy	Ethoxylated octylphenol / Polyethylene glycol octylphenyl ether / Polyoxyethylene (1,1,3,3-tetramethylbutyl)phenyl ether / tert-Octylphenol, ethoxylated	(CAS-No.) 9036-19-5	< 0.3	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 AquaticAcute 2, H401 AquaticChronic 2, H411
Cellulose, ethyl 2-hydroxyethylether	Ethulose / Ethylhydroxyethylcellulose	(CAS-No.) 9004-58-4	0.2	Comb. Dust
Distillates, petroleum, hydrotreated heavy naphthenic	Petroleum distillates, hydrotreated heavy naphthenic	(CAS-No.) 64742-52-5	0.15 – 0.2	Asp. Tox. 1, H304
Alcohols, C9-11, ethoxylated	Alkyl(C9-11) alcohol, ethoxylated / Polyethylene glycol, nonyl, decyl, undecyl ether	(CAS-No.) 68439-46-3	0.01 – 0.05	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 AquaticAcute 2, H401
Alcohols, C16-18, ethoxylated	Cetareth-10 / Ethoxylated cetylstearyl alcohol	(CAS-No.) 68439-49-6	0.01 – 0.05	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 AquaticAcute 1, H400
Ammoniumhydroxide	Ammonia, aqueous solution / Ammonium hydroxide ((NH4)(OH)) / Ammonia aqueous	(CAS-No.) 1336-21-6	≤ 0.03	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOTSE 3, H335 AquaticAcute 1, H400
Benzophenone	Benzoylbenzene / Diphenyl ketone / Methanone, diphenyl-	(CAS-No.) 119-61-9	0.01 – 0.03	Carc. 2, H351 STOT RE 2, H373 AquaticAcute 2, H401 AquaticChronic 3, H412
Solvent naphtha, petroleum, heavy aliphatic	Solvent naphtha (petroleum), heavy aliphatic / Solvent, heavy aliphatic / CCC-400 / Heavy aliphatic solvent naphtha	(CAS-No.) 64742-96-7	0.01 – 0.02	Flam. Liq. 4, H227 Asp. Tox. 1, H304

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Bromo-2-nitro-1,3-propanediol	Bronopol / Propane-1,3-diol, 2-bromo-2-nitro- / 1,3-Propanediol, 2-bromo-2-nitro- / 2-Bromo-2-nitropropane-1,3-diol / 2-BROMO-2-NITROPROPANE-1,3-DIOL / bronopol	(CAS-No.) 52-51-7	0.01 – 0.02	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOTSE 3, H335 AquaticAcute 1, H400 AquaticChronic 2, H411
Polyethyleneglycol	Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy- / PEG / Macrogols / Ethylene oxide polymer / 1,2-Ethanediol, homopolymer / Macrogol / PEG-9 / .alpha.-Hydro-.omega.-hydroxypoly(oxyethylene) / PEG-14 / .alpha.-Hydro-.omega.-hydroxypoly(oxy-1,2-ethanediyl) / Ethoxylated 1,2-ethanediol	(CAS-No.) 25322-68-3	< 0.02	STOTSE 3, H335
Residual Monomers:		(CAS-NO.) Trade Secret	< 0.01	STOTSE 3, H335 STOTRE 1, H372 Asp. Tox. 1, H304 AquaticAcute 3, H402 AquaticChronic 3, H412
1,2-Benzisothiazol-3(2H)-one	1,2-Benzisothiazolin-3-one / Benzisothiazolinone / 1,2-Benzisothiazolone	(CAS-No.) 2634-33-5	< 0.01	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 AquaticAcute 1, H400 AquaticChronic 1, H410 Comb. Dust
3(2H)-Isothiazolone, 2-methyl-	2-Methyl-3-isothiazolone / 3-Isothiazolone, 2-methyl-2-Methyl-2,3-dihydroisothiazol-3-one / 2-Methylisothiazol-3(2H)-one / 3(2H)-Isothiazolon-3-one, 2-methyl- / 2-Methylisothiazolin-3(2H)-one / N-Methyl-isothiazolone / methylisothiazolinone	(CAS-No.) 2682-20-4	< 0.01	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:dust,mist)H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOTSE 3, H335 AquaticAcute 1, H400 AquaticChronic 1, H410
Solvent naphtha, petroleum, light aromatic	Solvent naphtha (petroleum), light aromatic / Light aromatic solvent naphtha / Aromatic 100 / Hydrocarbons, C9, aromatics	(CAS-No.) 64742-95-6	< 0.01	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOTSE 3, H336 Asp. Tox. 1, H304 AquaticAcute 2, H401 AquaticChronic 2, H411
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)	Propane-1,3-diol, 2-ethyl-2-(hydroxymethyl)- / Propylidynetrimethanol / 1,1,1-Tris(hydroxymethyl)propane / TMP	(CAS-No.) 77-99-6	< 0.01	Not classified
2-Propenoic acid, sodium salt	Acrylic acid, sodium salt / Sodium acrylate / 2-Propenoic acid, sodium salt (1:1) / sodium acrylate	(CAS-No.) 7446-81-3	< 0.01	AquaticAcute 3, H402 AquaticChronic 3, H412

Toluene	Benzene, methyl- / Methylbenzene / Phenylmethane	(CAS-No.) 108-88-3	<0.001	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Methanol	Methyl alcohol / Carbinol / Methyl hydroxide / Wood alcohol	(CAS-No.) 67-56-1	<0.001	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation vapor), H331 STOT SE 1, H370

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injury: Skin sensitization

Symptoms/Injury After Inhalation: Prolonged exposure may cause irritation

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptom: This product contains Crystalline Silica and titanium dioxide dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica and titanium dioxide dust may cause lung damage in the form of silicosis, lung cancer, chronic kidney disease or respiratory irritation.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures

Explosion Hazard: Product is not explosive.

Reactivity: Quartz (silica) will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instruction: Use water spray or fog for cooling exposed containers

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection

Hazardous Combustion Products: Acrylic monomers. Metallic oxides. Carbon oxides (CO, CO₂). Acrid smoke and irritating fumes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

ARMAT Classic Plus

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedure: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection

Emergency Procedure: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: This product contains Crystalline Silica and titanium dioxide dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica and titanium dioxide dust may cause lung damage in the form of silicosis, lung cancer, chronic kidney disease, or respiratory irritation.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Chlorinated rubber.

7.3. Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL (TWA) (ppm)	(250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3)
Talc (Mg ₃ H ₂ (SiO ₃) ₄) (14807-96-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
USA IDLH	US IDLH (mg/m ³)	1000 mg/m ³ (containing no asbestos and <1% quartz)
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf ((not containing asbestos) containing <1% quartz, if 1%

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		quartz or more; use quartz limit) (See 29 CFR 1910.1000TABLE Z-3)
Carbonic acid, magnesium salt (1:1) (546-93-0)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust (Magnesite) 5 mg/m ³ (respirable dust (Magnesite)
Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	0.02 mg/l Parameter: Toluene- Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene- Medium: urine - Sampling time: end of shift 0.3 mg/g Kreatinin Parameter: o-Cresol with hydrolysis- Medium: urine - Sampling time: end of shift (background)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
USA NIOSH	NIOSH REL (TWA) [ppm]	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
USA NIOSH	NIOSH REL (STEL) [ppm]	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) [ppm]	300 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	500 ppm Peak (10 minutes)
Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA ACGIH	Biological Exposure Indices (BEI)	15 mg/l Parameter: Methanol- Medium: urine - Sampling time: end of shift (background, nonspecific)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
USA NIOSH	NIOSH REL (TWA) [ppm]	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) [ppm]	250 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
Polyethyleneglycol (25322-68-3)		
USA AIHA	WEEL TWA (mg/m ³)	10 mg/m ³ (molecular weight > 200 aerosol)
Limestone (1317-65-3)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Glass, oxide, chemicals (65997-17-3)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	3 fibers/cm ³ (fibers ≤ 3.5 μm in diameter & ≥ 10 μm in length), TWA

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		5mg/m3 (total)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ total dust, 5 mg/m ³ , respirable fraction 8 hr
Perlite (93763-70-3)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (General Industry- total dust)
Benzophenone(119-61-9)		
USA AIHA	WEEL TWA (mg/m ³)	0.5 mg/m ³
Residual Monomers:		
	Internal OEL Value(s)	Internal TWA: 4 ppm (Skin); Internal STEL: 10 ppm (Skin)
USA ACGIH	ACGIH TWA (ppm)	20 ppm

8.2. Exposure Controls

Appropriate Engineering Controls:

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protector

: Wear protective gloves.

Eye and Face Protector

: Chemical safety goggles.

Skin and Body Protector

: Wear suitable protective clothing.

Respiratory Protector

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: No data available
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Density	: 15.1 lb/gal
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity** Quartz (silica) will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.
- 10.2. Chemical Stability** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials** Strong acids, strong bases, strong oxidizers. Chlorinated rubber.
- 10.6. Hazardous Decomposition Products** Thermal decomposition may produce: Acrylic monomers. Carbon oxides (CO, CO₂). Acid smoke and irritating fumes. Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Aluminum hydroxide (Al(OH)₃) (21645-51-2)	
LD50 Oral Rat	> 5000 mg/kg
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5 mg/l/4h
Alcohols, C16-18, ethoxylated (68439-49-6)	
LD50 Oral Rat	1260 mg/kg
Alcohols, C9-11, ethoxylated (68439-46-3)	
LD50 Oral Rat	1400 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.28 mg/l/4h
2-Bromo-2-nitro-1,3-propanediol (52-51-7)	
LD50 Oral Rat	180 mg/kg
LD50 Dermal Rat	1600 mg/kg
LC50 Inhalation Rat	> 5 g/m ³ (Exposure time: 6 h)
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
LD50 Oral Rat	120 mg/kg
LD50 Dermal Rabbit	200 mg/kg
LC50 Inhalation Rat	0.11 mg/l/4h
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
LD50 Oral Rat	1020 mg/kg
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 Oral Rat	8400 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	3400 ppm/4h
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)	
LD50 Oral Rat	14100 mg/kg
Toluene (108-88-3)	
LD50 Oral Rat	2600 mg/kg
LD50 Dermal Rabbit	12000 mg/kg

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC50 InhalationRat	25.7 mg/l/4h
ATE (Dermal)	12,000.00mg/kg body weight
Methanol(67-56-1)	
LD50 DermalRabbit	15840 mg/kg
LC50 InhalationRat	22500 ppm (Exposure time: 8 h)
ATE (Oral)	100.00 mg/kg body weight
ATE (Dermal)	300.00 mg/kg body weight
ATE (Vapors)	3.00 mg/l/4h
Titaniumdioxide(13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Polyethyleneglycol(25322-68-3)	
LD50 Oral Rat	22 g/kg
LD50 DermalRabbit	> 20 g/kg
Poly(oxy-1,2-ethanediyl),.alpha.-[(1,1,3,3-tetramethylbutyl)pheny-.omega.-hydroxy- (9036-19-5)	
LD50 Oral Rat	1700 mg/kg
2,2,4-Trimethylpentan-1,3-diol monoisobutyrate(25265-77-4)	
LD50 Oral Rat	3200 mg/kg
LD50 Dermal Rat	> 15200 mg/kg
LC50 InhalationRat	> 3.55 mg/l (Exposure time: 6 h)
Perlite(93763-70-3)	
LD50 Oral Rat	12960 mg/kg (Mouse)
Benzophenone(119-61-9)	
LD50 Oral Rat	> 10 g/kg
LD50 DermalRabbit	3535 mg/kg
Ammoniumhydroxide(1336-21-6)	
LD50 Oral Rat	350 mg/kg

Skin Corrosion/Irritation Not classified

Serious Eye Damage/Irritation Not classified

Respiratory or Skin Sensitizer: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified.

Quartz(14808-60-7)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Talc (Mg3H2(SiO3)4)(14807-96-6)	
IARC group	3
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
Toluene(108-88-3)	
IARC group	3
Titaniumdioxide(13463-67-7)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Glass, oxide, chemicals(65997-17-3)	
IARC group	3
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Benzophenone(119-61-9)	
IARC group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: This product contains Crystalline Silica and titanium dioxide dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica and titanium dioxide dust may cause lung damage in the form of silicosis, lung cancer, chronic kidney disease or respiratory irritation.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Talc (Mg₃H₂(SiO₃)₄) (14807-96-6)	
LC50 Fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydaniorerio [semi-static])
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Alcohols, C9-11, ethoxylated (68439-46-3)	
LC50 Fish 1	6 – 12 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	2.217 – 3.523 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2-Bromo-2-nitro-1,3-propanediol (52-51-7)	
ErC50 (Algae)	0.15 mg/l (Species: Skeletonema costatum)
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
EC50 Daphnia 1	0.99 mg/l
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)	
EC50 Daphnia 1	13000 mg/l (Exposure time: 48 h - Species: Daphnia species)
EC50 Daphnia 2	10330 – 16360 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Toluene (108-88-3)	
LC50 Fish 1	15.22 (15.22 – 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 (5.46 – 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC Chronic Fish	1.4 mg/l (Oncorhynchus kisutch)
NOEC Chronic Crustacea	0.74 mg/l (Ceriodaphnia dubia)
Methanol (67-56-1)	
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	1340 mg/l
LC50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy (9036-19-5)	
LC50 Fish 1	7.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	8.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])
NOEC Chronic Fish	0.084 ppm
NOEC Chronic Crustacea	0.037 ppm
2-Propenoic acid, sodium salt (7446-81-3)	
LC50 Fish 1	27 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
2,2,4-Trimethylpentan-1,3-diol monoisobutyrate (25265-77-4)	
LC50 Fish 1	30 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	33 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ErC50 (Algae)	18.4 mg/l
NOEC Chronic Algae	3.28 mg/l
Benzophenone(119-61-9)	
LC50 Fish 1	13.2 – 15.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
ErC50 (Algae)	3.53 mg/l
NOEC Chronic Crustacea	0.2 mg/l
Ammoniumhydroxide(1336-21-6)	
LC50 Fish 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.66 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.66 mg/l (Exposure time: 48 h - Species: Daphnia pulex)
NOEC Chronic Crustacea	3.47 mg/l

12.2. Persistence and Degradability

ARMAT Classic Plus	
Persistence and Degradability	Not established
Residual Monomers	
Persistence and Degradability	Readily biodegradable

12.3. Bioaccumulative Potential

ARMAT Classic Plus	
Bioaccumulative Potential	Not established
Talc (Mg₃H₂(SiO₃)₄)(14807-96-6)	
BCF Fish 1	(no known bioaccumulation)
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.3 (at 25 °C)
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)	
BCF Fish 1	0.14
Partition coefficient n-octanol/water (Log Pow)	-2.37
Toluene(108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.7
Methanol(67-56-1)	
BCF Fish 1	< 10
Partition coefficient n-octanol/water (Log Pow)	-0.77
2,2,4-Trimethylpentan-1,3-diol monoisobutyrate(25265-77-4)	
Partition coefficient n-octanol/water (Log Pow)	3.47 (at 25 °C)
Benzophenone(119-61-9)	
BCF Fish 1	3.4 – 9.2
Partition coefficient n-octanol/water (Log Pow)	3.2
Residual Monomers	
Partition coefficient n-octanol/water (Log Pow)	0.93

12.4. Mobility in Soil

Residual Monomers	
Partition coefficient n-octanol/water (Log Koc)	15

12.5. Other Adverse Effects

Other Information : Avoid release to the environment

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendation: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology - Waste Material: Avoid release to the environment

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Aluminum hydroxide (Al(OH)₃) (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Talc (Mg₃H₂(SiO₃)₄) (14807-96-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Carbonic acid, magnesium salt (1:1) (546-93-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cellulose, ethyl 2-hydroxyethyl ether (9004-58-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Alcohols, C16-18, ethoxylated (68439-49-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Alcohols, C9-11, ethoxylated (68439-46-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Bromo-2-nitro-1,3-propanediol (52-51-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene(108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLARQ	1000 lb
SARA Section 313 - Emission Reporting	1 %
Methanol(67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLARQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
Titaniumdioxide(13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyethyleneglycol(25322-68-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Poly(oxy-1,2-ethanediyl),.alpha.-[[1,1,3,3-tetramethylbutyl]pheny]-.omega.-hydroxy (9036-19-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Limestone(1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Propenoic acid, sodium salt (7446-81-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Glass, oxide, chemicals(65997-17-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2,2,4-Trimethylpentan-1,3-diol monoisobutyrate(25265-77-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Benzophenone(119-61-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ammoniumhydroxide(1336-21-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLARQ	1000 lb

15.2. US State Regulations

Quartz(14808-60-7)
U.S. - Massachusetts- Right To Know List U.S. - New Jersey- Right to Know Hazardous Substance List U.S. - Pennsylvania- RTK (Right to Know) List
Talc (Mg3H2(SiO3)4)(14807-96-6)
U.S. - Massachusetts- Right To Know List U.S. - New Jersey- Right to Know Hazardous Substance List U.S. - Pennsylvania- RTK (Right to Know) List
Carbonic acid, magnesium salt (1:1) (546-93-0)
U.S. - Massachusetts- Right To Know List U.S. - New Jersey- Right to Know Hazardous Substance List
Toluene(108-88-3)
U.S. - Massachusetts- Right To Know List U.S. - New Jersey- Right to Know Hazardous Substance List U.S. - Pennsylvania- RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania- RTK (Right to Know) List
Methanol(67-56-1)
U.S. - Massachusetts- Right To Know List

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania- RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania- RTK (Right to Know) List

Titaniumdioxide(13463-67-7)

U.S. - Massachusetts- Right To Know List
 U.S. - New Jersey- Right to Know Hazardous Substance List
 U.S. - Pennsylvania- RTK (Right to Know) List

Limestone(1317-65-3)

U.S. - Massachusetts- Right To Know List
 U.S. - New Jersey- Right to Know Hazardous Substance List
 U.S. - Pennsylvania- RTK (Right to Know) List

Perlite(93763-70-3)

U.S. - Massachusetts- Right To Know List
 U.S. - New Jersey- Right to Know Hazardous Substance List
 U.S. - Pennsylvania- RTK (Right to Know) List

Ammoniumhydroxide(1336-21-6)

U.S. - Massachusetts- Right To Know List
 U.S. - New Jersey- Right to Know Hazardous Substance List
 U.S. - Pennsylvania- RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania- RTK (Right to Know) List

California Proposition 65



WARNING: This product can expose you to Benzophenone, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Toluene (108-88-3)		X		
Methanol (67-56-1)		X		
Titanium dioxide (13463-67-7)	X			
Benzophenone (119-61-9)	X			

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revisor : 10/28/2020
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200. The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

GHS Full Text Phrases:

Acute Tox. 2 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation vapor)	Acute toxicity (inhalation: vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment- Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment- Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment- Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment- Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment- Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment- Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1

ARMAT Classic Plus

Safety Data Sheet



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carc. 1A	CarcinogenicityCategory1A
Carc. 2	CarcinogenicityCategory2
Comb. Dust	CombustibleDust
Eye Dam. 1	Serious eye damage/eyeirritationCategory1
Eye Irrit. 2A	Serious eye damage/eyeirritationCategory2A
Flam. Liq. 2	Flammableliquids Category2
Flam. Liq. 4	Flammableliquids Category4
Met. Corr. 1	Corrosiveto metals Category1
Repr. 2	Reproductivetoxicity Category2
Skin Corr. 1B	Skin corrosion/irritationCategory1B
Skin Irrit. 2	Skin corrosion/irritationCategory2
Skin Sens. 1	Skin sensitization,Category1
Skin Sens. 1A	Skin sensitization,category1A
STOT RE 1	Specific target organ toxicity (repeated exposure)Category1
STOT RE 2	Specific target organ toxicity (repeated exposure)Category2
STOT SE 1	Specific target organ toxicity (single exposure)Category1
STOT SE 3	Specific target organ toxicity (single exposure)Category3
STOT SE 3	Specific target organ toxicity (single exposure)Category3
H225	Highly flammableliquid and vapor
H227	Combustibleliquid
H290	May be corrosiveto metals
H301	Toxic if swallowec
H302	Harmfulif swallowec
H304	May be fatal if swallowedand enters airways
H311	Toxic in contact with skin
H312	Harmfulin contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritator
H317	May cause an allergicskin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritator
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratoryirritator
H336	May cause drowsinessor dizziness
H350	May cause cancer
H351	Suspectedof causing cancer
H361	Suspectedof damagingfertilityor the unborn child
H370	Causes damageto organs
H372	Causes damageto organs through prolongedor repeatedexposure
H373	May cause damageto organs through prolongedor repeatedexposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmfulto aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmfulto aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.