

## StoTherm® ci over Wood-Frame Flanged Window-Head

Stud Cavity Insulation Wood Framing Sto EPS Insulation Board, Pre-Wrapped Around Opening StoGuard® Detail Component Sto EPS Insulation Board Flashing StoGuard® Detail Component Continuous Air Seal Around Entire Perimeter Backer Rod & Sealant Weather Seals (Entire Perimeter with Weeps Between Underside of Trim & Flashing Leg) Window Assembly Sto Finish Spray Polyurethane Foam Insulation Sto Primer Continuous Bead of Sealant Behind Mounting Flange (Jambs and Head Only) (Optional) Sto Mesh Sto Adhesive Sto Base Coat StoGuard® Air and Water-Resistive Barrier (with Sto Mesh Embedded) StoGuard® Detail Component Sheathing Step 3 - Cladding and Perimeter Weather and Air Seals

## Notes:

1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.

Detail No.: 52w.24B-3

Date: July 2022

- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

## **ATTENTION**

Property of Sto Corp. All Rights Reserved

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

www.stocorp.com