

StoTherm® ci Sign Attachment

Sto TurboStick® Adhesive Light Gauge Steel Stud Framing Sheathing StoGuard® Air and Water-Resistive Barrier XPS Insulation Board Sto Base Coat (with Sto Mesh Embedded) Sto Mesh Sto Primer (Optional) Sto Finish Washer Behind Sign Set in Sealant Sign Wood Blocking Hole Drilled in EIFS Bolt w/ Washers at Each End and Lined with Sealant Neutral Cure Sealant PVC or Stainless Steel Sleeve (Sleeve Extends From Finish Through Blocking, Shown Partial Length for Clarity)

Notes:

1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.

Detail No.: 53s.71

Date: September 2022

- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

ATTENTION

Property of Sto Corp. All Rights Reserved

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

www.stocorp.com