

Building with conscience.

Sto Exterior Coatings for Concrete & Concrete Masonry Unit (CMU)



Detail No.: EPD 30c.00 Date: December 2019

Concrete Masonry Unit (CMU)	Notes: A. Details shows the installa- tion of Sto Exterior Coatings.
Sto BTS Plus Base Coat	B. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.
with Sto Mesh embedded Sto Finish (See Sto Product 3)	C. Concrete masonry unit (CMU) wall shall be clean and free of efflorescence, dirt and any other materials that may affect the bond of the coatings to the CMU surface.
	D. Remove mortar droppings and repair any defects that will affect the final appearance of the wall finish.
	E. Apply Sto Basecoat to the CMU and allow to cure for a minimum of 24 hours.
	F. Install Sto Finish coat and allow to dry.
	G. Protect coatings from rain, freezing, and continuous high humidity until completely dry.
	H. There are no substitutions for the Sto products listed below.
	Sto Products:
	1. Sto Mesh
	2. Sto BTS Plus Base Coat
	3. Sto Finish Components:
	a. Stolit [®] & Stolit [®] Dark Colors: 1.0, 1.5, R1.5 and Freeform b. Stolit [®] Lotusan & Stolit [®] Lotusan Dark Colors: 1.0, 1.5, R1.5 and Freeform
Property of Sto Corp. All Rights Reserved.	www.stocorp.com

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperty, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

