

StoVentro[™] Sub-Construction System Date: May 2021 Installation at Window Jamb with Backer Rod and Sealant Joint Plan View Detail No.: 90.Sc.085 Structural wall assembly (concrete, masonry, stud wall with sheathing) StoGuard[®] Air & Moisture Barrier Mineral wool insulation Anchoring element in accordance with structural analysis StoVentro Bracket StoVentro T-Profile StoVentro Sub-construction Screw with self-drilling and over-tightening protection Facade/Cladding Panel Attachment (by panel mfr) Facade/Cladding Panel (by panel mfr) Install Sto L-Profile as needed to stiffen corner Backer Rod and Sealant Joint (by others) Metal window sill (by others) ≤ 16" (≤ 406mm)

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp.website, www.stocorp.com.