



Building with conscience.

Sto Corp.
3800 Camp Creek Parkway
Building 1400, Suite 120
Atlanta, GA 30331

Addendum to StoPowerwall Specification Nos.: 6200, 6300, 6400, 6500, 6600, 6700, 6800

This addendum lists StoPowerwall branded stucco blends, and unbranded blends covered in the Sto Corp. stucco warranty program

	Product Name and Description	Manufacturer	Product Data	<ul style="list-style-type: none"> Mix: H20 / Bag / Sand Mix: (Time) Mix: (Yield)¹ 	Code Compliance ²	Comments
One Coat Stucco (pre-sanded)	102 StoPowerwall Stucco Pre-Blended – a controlled blend of portland cement, fibers, graded sand, and chemical additives	Old Castle DBA Amerimix 8201 Arrowbridge Boulevard Charlotte, NC 28723	102 StoPowerwall Stucco Pre-Blended	<ul style="list-style-type: none"> 1-1.5 gal / 80 lb (3-5 minutes) (10-12 ft² at ¾ inch) 		
	Quikrete One Coat Fiberglass Reinforced Stucco – Sanded (no. 1200-80) – alkali resistant fiberglass reinforced portland cement based one coat stucco	The QUIKRETE Companies 5 Concourse Parkway Suite 1900 Atlanta, GA 30328	Quikrete 1200 Data Sheet	<ul style="list-style-type: none"> 5.5 - 6.5 qts / 80 lb / 210-250 lb (3-5 minutes) (10-12 ft² at ¾ inch) 	IAPMO 455	Refer to ICC ESR for wind loads, use on noncombustible construction and on fire-resistance rated walls
One Coat Stucco (concentrate)	103 StoPowerwall Stucco – controlled blend of Portland cement, fibers, and chemical additives	Holcim US, Inc. 200 Safety Street / Highway 453 Holly Hill, SC 29059	103 StoPowerwall Stucco	<ul style="list-style-type: none"> 5-6.5 gal / 80 lb / 200-240 lb (3-5 minutes) 30-40 ft² at ¾ inch 	ICC ESR 2323	Refer to ICC ESR wind loads, use on noncombustible construction and on fire-resistance rated walls.
	103 StoPowerwall Stucco – controlled blend of Portland cement, fibers, and chemical additives	Old Castle DBA Amerimix 8201 Arrowbridge Boulevard Charlotte, NC 28723	103 StoPowerwall Stucco	<ul style="list-style-type: none"> 4-6 gal / 80 lb / 2.5 – 3 cu. ft. (180-240 lbs) (3-5 minutes) 35-40 ft² at ¾ inch 		
	103 StoPowerwall Stucco (Western 1-Kote Gray Concentrate) – fiber reinforced portland cement-based one coat stucco concentrate	Sacramento Stucco Company 1550 Parkway Blvd. West Sacramento, CA 95691	Western 1-Kote Gray Concentrate Data Sheet	<ul style="list-style-type: none"> 4 gal / 80 lb / 200 lb (Minimum 5 minutes) (30-40 ft² at ¾ inch) 	IAPMO ER 382	Refer to ICC ESR for wind loads, use on noncombustible construction and on fire-resistance rated walls.
	EZ Concentrate – portland cement-based, fiber reinforced one coat stucco concentrate	Adams Supply 2722 Logan Street Dallas, TX 75215	EZ Concentrate Data Sheet	<ul style="list-style-type: none"> 5-7 gal / 80 lb / 200 – 250 lb (3-5 minutes) 27 ft² at ¾ inch 	ICC ESR 2477	Limited to Type V Construction. Refer to ICC ESR. Refer to ICC ESR for wind loads and on fire-resistance rated walls
Scratch and Brown Coat Stucco	Amerimix Fiber Scratch & Brown Stucco Concentrate (no. 745) – Portland cement based fiber reinforced stucco concentrate for scratch and brown coat applications	Old Castle DBA Amerimix 8201 Arrowbridge Boulevard Charlotte, NC 28723	Fiber Scratch & Brown Stucco	<ul style="list-style-type: none"> 4-6.6 gal / 94 lbs. / 2.5 -4 cu.ft. (3-5 minutes) 40-65 ft² at ¾ inch Use 3.0-4 cu.ft. sand for brown coat		
	Quikrete Base Coat Stucco – Pump Grade (no. 1139-86) – flowable portland cement based stucco designed for hand and spray scratch and brown coat applications	The QUIKRETE Companies 5 Concourse Parkway Suite 1900 Atlanta, GA 30328	Quikrete 1139 Data Sheet	<ul style="list-style-type: none"> 1.5 gal / 80 lb (2-3 minutes) 10-12 ft² at ¾ inch 	Complies with ASTM C 926 ³	
	108 Powerwall Scratch & Brown (Western Top Gun Premium Plaster) – base coat for conventional stucco designed to be a pump grade product.	Sacramento Stucco Company 1550 Parkway Blvd. West Sacramento, CA 95691	Top Gun Premium Plaster Data Sheet	<ul style="list-style-type: none"> 2.75 – 3.25 Gal 1/3 cement/sand 3.75 – 4.25 Gal 1/4 cement/sand (3-5 minutes) 40-50 ft² at ¾ inch 	Complies with ASTM C 926 ³	
	108 Powerwall Scratch & Brown (IPC Scratch & Brown) – portland cement-based stucco concentrate for scratch and brown coat applications	IPC Building Products 10202 Synott Road Sugar Land, Texas 77478	IPC Building Products	<ul style="list-style-type: none"> Wkblty / 94 lb / 3.25 – 3.5 cu ft (6 minutes) (70-80 ft² at ¾ inch) 		
	EZ Scratch & Brown w/fiber – portland cement-based, fiber reinforced stucco concentrate for scratch and brown coat applications	Adams Supply 2722 Logan Street Dallas, TX 75215	EZ Scratch & Brown Data Sheet	<ul style="list-style-type: none"> 5-7 gal / 80 lb / 200 – 250 lb (3-5 minutes) 27 ft² at ¾ inch 	Complies with ASTM C 926 ³	

1. Yield will vary with application technique, surface conditions, substrate variances from required tolerances, and other variables that may exist.

2. IMPORTANT: ICC ESRs should be consulted concerning use, application, and limitations associated with one coat stucco products

3. Compliance with ASTM C 926 relates to conformance with mix ratio requirements. Installation and other aspects of C926 such as stucco thickness must be followed for full compliance.

4. Use of admixtures, bonding agents, air-entraining agents, or any other additives is not permitted as they may affect properties and workability.