

StoPowerwall[®]ci

Floorline with Deflection Track

Metal Frame Code Compliant Paper or Felt WRB (water-resistive barrier) XPS Insulation Board Sto DrainScreen® Not to scale Galvanized Self-Furred Diamond Mesh StoGuard®Detail Component StoPowerwall® Brown Coat Casing Bead Sill Flashing Backer Rod & Sealant StoPowerwall®Scratch Coat StoGuard®Air and Water-Resisitive Barrier Glass Mat Gypsum Sheathing (ASTM C1177 Compliant) Sto Textured Finish Sto Primer Not to scale

Notes:

1. Refer to StoGuard® Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.

Detail No.: 62s.09.2D

Date: July 2022

- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Glass mat gypsum sheathing in compliance with ASTM C1177, exterior grade and Exposure 1 wood based sheathing, or cementitious sheathing in compliance with ASTM C1325.
- 4. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved WWW.stocorp.com

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.