

## StoPowerwall® ExtraSeal® Aesthetic Feature For feature thickness of greater than 2"(>50mm)

Sto ExtraSeal® Skim Coat Masonry Substrate Water-Resistive Air Barrier (See Note 1) Sto ExtraSeal® Scratch Coat Sto Powerwall® **Brown Coat** (See Note 3) Minimum 2 ½ inch (54mm) Overlap Minimum 1:2 slope StoColor Acryl Plus Note: requires two coats Sto Textured Finish Note: requires two coats of StoColor Acryl Plus Greater than along slope as noted 2" (>50mm) Sto Primer (Optional except where Sto Flexyl is applied.) See Note 5 Sto Flexyl® with Sto Mesh embedded Sto Base Coat with Sto Mesh embedded Foam Trim Sto EPS Insulation Board (attached with Sto Adhesive)

## **Notes:**

1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construc-

Detail No.: 65c.60B

**Date: January 2025** 

- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Stucco brown coat material in compliance with ASTM C926 and manufactured or listed by Sto Corp.
- 4. Refer to applicable Sto guide specifications, product bulletins, Tech Hotlines, and other Sto guide details for additional information.
- 5. Sto Primer is required for Sto Specialty Finishes such as Sto GraniTex, StoSignature Brick, and others. Refer to specific Sto finish product bulletins.
- 6. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

ATTENTION

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.



